



Turnitin Originality Report

CLAY2105 by Suryadi Ismadji

From journal (Hippo-hippo)

Processed on 15-Feb-2018 17:54 WIB

ID: 916388867

Word Count: 4879

Similarity Index 17%	Similarity by Source	
	Internet Sources:	8%
	Publications:	17%
	Student Papers:	3%

sources:

1

1% match (publications)

[Li, Y.. "Preparation, characterization and application of heterogeneous solid base catalyst for biodiesel production from soybean oil", Biomass and Bioenergy, 201107](#)

2

1% match (Internet from 16-Jan-2017)

http://file.scirp.org/pdf/MSA_2017011116351891.pdf

3

1% match (publications)

[Borges, M.E.. "Recent developments on heterogeneous catalysts for biodiesel production by oil esterification and transesterification reactions: A review", Renewable and Sustainable Energy Reviews, 201206](#)

4

1% match (publications)

[Lukic, I.. "Alumina/silica supported K²CO³ as a catalyst for biodiesel synthesis from sunflower oil", Bioresource Technology, 200910](#)

5

1% match (publications)

[Liu, H.. "Cinder supported K²CO³ as catalyst for biodiesel production", Applied Catalysis B, Environmental, 20110811](#)

6

1% match (publications)

[Kurniawan, Fredi, Michael Wongso, Aning Ayucitra, Felycia Edi Soetaredjo, Artik Elisa Angkawijaya, Yi-Hsu Ju, and Suryadi Ismadji. "Carbon microsphere from water hyacinth for supercapacitor electrode", Journal of the Taiwan Institute of Chemical Engineers, 2015.](#)

7

1% match (publications)

[Kaki, Shiva, and R Prasad. "BASE CATALYZED TRANSESTERIFICATION FOR BIODIESEL: NOVEL CATALYST OPTIONS", Industrial Catalysis and Separations, 2014.](#)

8

1% match (publications)

[Xie, W.. "Transesterification of soybean oil catalyzed by potassium loaded on alumina as a solid-base catalyst", Applied Catalysis A, General, 20060120](#)

1% match (publications)

9

[Agarwal, M.. "Study of catalytic behavior of KOH as homogeneous and heterogeneous catalyst for biodiesel production", Journal of the Taiwan Institute of Chemical Engineers, 201201](#)

10

1% match (publications)

[Li, Xiaoshuan, Dinghua Yu, Wengui Zhang, Zhengwen Li, Xiaowei Zhang, and He Huang. "Effective synthesis of cis-3-hexen-1-yl acetate via transesterification over KOH/ \$\gamma\$ -Al₂O₃: Structure and catalytic performance", Applied Catalysis A General, 2013.](#)

11

< 1% match (student papers from 04-Feb-2014)

[Submitted to Khon Kaen University on 2014-02-04](#)

12

< 1% match (Internet from 30-Aug-2017)

<https://www.omicsonline.org/open-access/effectiveness-of-enzymatic-transesterification-of-beef-tallow-using-2324-6679.1000116.pdf>

13

< 1% match (publications)

[Lee, H.V.. "Process optimization design for jatropha-based biodiesel production using response surface methodology", Fuel Processing Technology, 201112](#)

14

< 1% match (Internet from 19-Feb-2014)

<http://www.google.com/patents/US20090118236>

15

< 1% match (Internet from 20-Sep-2017)

<http://scholarcommons.usf.edu/cgi/viewcontent.cgi?article=7276&context=etd>

16

< 1% match (publications)

[Matthew S. Muroski, Om V. Singh. "chapter 21 Implications of Nanotechnology into Next Generation Biofuel Industry", IGI Global, 2015](#)

17

< 1% match (Internet from 27-Nov-2017)

<http://hrcak.srce.hr/file/265126>

18

< 1% match (publications)

[Thanh, Le Tu, Kenji Okitsu, Luu Van Boi, and Yasuaki Maeda. "Catalytic Technologies for Biodiesel Fuel Production and Utilization of Glycerol: A Review", Catalysts, 2012.](#)

19

< 1% match (publications)

[Rahmawati, Astrid, Debora Pang, Yi-Hsu Ju, Felycia Edi Soetaredjo, Ong Lu Ki, and Suryadi Ismadji. "Supercritical CO₂ Extraction of Phytochemical Compounds from Mimosa pudica Linn", Chemical Engineering Communications, 2015.](#)

20

< 1% match (Internet from 07-Sep-2017)

<http://digitalcommons.usu.edu/cgi/viewcontent.cgi?article=2420&context=etd>

- 21 < 1% match (publications)
[Balaram, M.. "Acetylation of glycerol to synthesize bioadditives over niobic acid supported tungstophosphoric acid catalysts", Fuel Processing Technology, 201002](#)
-
- 22 < 1% match (publications)
[Kumar, J. Kanna, P. Mallikarjuna Reddy, and K. Hemachandra Reddy. "Experimental Evaluation of Performance and Emissions of CI Engine Using Cottonseed Biodiesel with N-Butonal as a Additive", Advanced Materials Research, 2014.](#)
-
- 23 < 1% match (student papers from 18-Jul-2014)
[Submitted to Indian Institute of Technology Guwahati on 2014-07-18](#)
-
- 24 < 1% match (publications)
["Catalysis for Alternative Energy Generation", Springer Nature, 2012](#)
-
- 25 < 1% match (publications)
[Han, B.. "Oligonucleotide-stabilized fluorescent silver nanoclusters for sensitive detection of biothiols in biological fluids", Biosensors and Bioelectronics, 20110115](#)
-
- 26 < 1% match (publications)
[Lin, Jianming, Qunwei Tang, Jihuai Wu, and Hui Sun. "Synthesis, characterization and properties of polyaniline/expanded vermiculite intercalated nanocomposite", Science and Technology of Advanced Materials, 2008.](#)
-
- 27 < 1% match (publications)
[Patel, Hasmukh A.. "Synthesis and characterization of organic bentonite using Gujarat and Rajasthan clays", Current Science \(00113891\)/00113891, 20070410](#)
-
- 28 < 1% match (Internet from 21-Sep-2017)
<http://repositorio.ufsm.br/bitstream/handle/1/8811/SIMOES%2c%20SANTHIAIGO%20SCHERER.pdf?isAllowed=y&sequence=1>
-
- 29 < 1% match (publications)
[Shin, H.Y.. "Transesterification of used vegetable oils with a Cs-doped heteropolyacid catalyst in supercritical methanol", Fuel, 201206](#)
-
- 30 < 1% match (Internet from 17-Feb-2017)
http://eprints.kfupm.edu.sa/140228/1/Usman_Abdulhafiz.pdf
-
- 31 < 1% match (Internet from 18-Jun-2017)
http://eprints.uwe.ac.uk/28899/1/Cement%20Stabilisation%20of%20Crude%20Oil-Contaminated%20Soils_final.pdf
-

- 32** < 1% match (publications)
[Kouzu, M.. "Transesterification of vegetable oil into biodiesel catalyzed by CaO: A review", Fuel, 201203](#)
-
- 33** < 1% match (Internet from 23-Oct-2014)
http://www.iscientific.org/Vol_4_2013/10%20JICBS-13-04-13.pdf
-
- 34** < 1% match (Internet from 31-Aug-2017)
<http://nopr.niscair.res.in/bitstream/123456789/12473/1/IJCA%2050A%288%29%201017-1025.pdf>
-
- 35** < 1% match (Internet from 18-Nov-2016)
<https://biotechnologyforbiofuels.biomedcentral.com/articles/10.1186/1754-6834-7-55>
-
- 36** < 1% match (Internet from 16-May-2016)
<http://www.ajas.info/journal/view.php?number=22689&viewtype=pubreader>
-
- 37** < 1% match (publications)
[Miladinović, Marija R., Olivera S. Stamenković, Predrag T. Banković, Aleksandra D. Milutinović-Nikolić, Dušan M. Jovanović, and Vlada B. Veljković. "Modeling and optimization of sunflower oil methanolysis over quicklime bits in a packed bed tubular reactor using the response surface methodology", Energy Conversion and Management, 2016.](#)
-
- 38** < 1% match (publications)
[Xu, Guizhuan, Xiaoyan Cui, Shuaiyao Fan, Bailiang Zhang, Huamin Song, Xiaobin Yan, Xiaoqin Ma, and Dechuan Kong. "Optimization of Transesterification of Beef Tallow for Biodiesel Production", 2011 Asia-Pacific Power and Energy Engineering Conference, 2011.](#)
-
- 39** < 1% match (publications)
[Feyzi, Mostafa, and Zahra Shahbazi. "Preparation, kinetic and thermodynamic studies of Al-Sr nanocatalysts for biodiesel production", Journal of the Taiwan Institute of Chemical Engineers, 2016.](#)
-
- 40** < 1% match (publications)
[Lee, J.S.. "Biodiesel production by heterogeneous catalysts and supercritical technologies", Bioresource Technology, 201010](#)
-
- 41** < 1% match (publications)
[B. I. Olu-Owolabi. "Removal of Cu²⁺ and Cd²⁺ from Aqueous Solution by Bentonite Clay Modified with Binary Mixture of Goethite and Humic Acid", Water Air and Soil Pollution, 01/23/2010](#)
-
- 42** < 1% match (publications)
[Palligarnai T. Vasudevan. "Environmentally Sustainable Biofuels: Advances in Biodiesel Research", Waste and Biomass Valorization, 02/04/2010](#)

paper text:

This article appeared in a journal published by Elsevier. The attached copy is furnished to the author for internal non-commercial research and education use, including for instruction at the authors institution and sharing with colleagues. Other uses, including reproduction and distribution, or selling or licensing copies, or posting to personal, institutional or third party websites are prohibited. In most cases authors are permitted to post their version of the article (e.g. in Word or Tex form) to their personal website or institutional repository. Authors requiring further information regarding Elsevier's archiving and manuscript policies are encouraged to visit: <http://www.elsevier.com/copyright> Applied Clay Science 53 (2011) 341–346 Contents lists available at ScienceDirect Applied Clay Science journal homepage: www.elsevier.com/locate/clay Note KOH/bentonite

7catalysts for transesterification of palm oil to biodiesel

Felycia Edi Soetaredjo *, Aning Ayucitra, Suryadi Ismadji, Anastasia Lidya Maukar

6Department of Chemical Engineering, Widya Mandala Surabaya Catholic University, Kalijudan 37, Surabaya 60114, Indonesia

article info Article history: Received 2 June 2010 Received in revised form 9 December 2010 Accepted 11 December 2010 Available online 20 December 2010

32Keywords: Biodiesel Transesterification Solid base Catalyst

Bentonite Palm Oil Potassium hydroxide abstract A potential application of KOH/bentonite as a

32catalyst for biodiesel production was studied.

A series of KOH/ bentonite catalysts was prepared by impregnation of bentonite from Pacitan with potassium hydroxide. The ratios between KOH and bentonite were 1:20, 1:10, 1:5, 1:4, 1:3, and 1:2. The characterization of KOH/ bentonite and natural bentonite was conducted by nitrogen adsorption and XRD analysis.

4The effects of various reaction variables on the yield of biodiesel were investigated.

The highest yield of biodiesel over KOH/ bentonite catalyst was $90.70 \pm 2.47\%$. It was obtained at KOH/bentonite 1:4, reaction time of 3 h, 3% catalyst,

37 **methanol to oil ratio of 6, and the reaction temperature at 60**

°C. © 2010 Elsevier B.V. All rights reserved. 1. Introduction Biodiesel development has gained the attention of researchers in recent years because of the rate of depletion of fossil fuel (Zhou et al., 2008). Biodiesel is noteworthy for its similarity

29 **to petroleum- based diesel. It can be used in diesel engines without engine modification.** The production of **biodiesel**

is performed either through

42 **transesterification of triglycerides using alcohol in the presence of a catalyst**

(Kim et al., 2010) or deoxygenative ecofining of triglycerides in a non alcohol environment (Ong and Bhatia, 2010). Different catalysts have been explored and used for biodiesel production from seed oils using homogenous bases such as potassium hydroxide and sodium hydroxide (Saravanan

25 **et al., 2009; Shiu et al., 2010),**

homogenous acids such as sulfuric acid (Saravanan

25 **et al., 2009; Shiu et al., 2010),**

heterogeneous solid catalysts such as cation-exchange resin and hydrotalcites (Dhainaut

16 **et al., 2010; Feng et al., 2010; Gao et al., 2010; Guo et al., 2010; Liu et al., 2010; Silva et al., 2010; Sun et al.,**

2010), and enzymes such as *C. antarctica* (Novozym 435) and lipase (Ranganathan et al., 2008; Talukder et al., 2010). The conventional

15 **commercial process used for biodiesel production is base catalyzed transesterification.**

However, homogeneous base catalysts such as sodium hydroxide for the production of biodiesel cannot be recovered or regenerated after the reaction and also produce toxic wastewater. Heterogeneous solid

catalysts have been studied as substitutes for homogeneous catalysts, and have the advantage of being easy to recover and reuse. They are also more environmentally friendly. The * Corresponding author. Tel.: +62 313891264; fax: +62 313891267. E-mail address: felyciae@yahoo.com (F.E. Soetaredjo). 0169-1317/\$

8see front matter © 2010 Elsevier B.V. All rights reserved. doi:10.1016/j.

clay.2010.12.018 heterogeneous solid catalysts commonly used for biodiesel production are categorized into several types: solid alkali catalyst (Guo et al., 2010; Hsieh et al., 2010; Samart et al., 2010), solid acid catalyst (Leung et al., 2010; Sun et al., 2010), mesoporous silica support catalyst (Dhainaut et al., 2010), and alkali support catalyst (Samart et al., 2010; Zabeti et al., 2010). Solid alkali catalysts commonly used in biodiesel preparation are calcium oxide (Samart et al., 2010), and calcined sodium silicate (Guo et al., 2010). Some of these catalysts are promising while some others still show lower performance than homogeneous catalysts in the terms of activity and FAME yield. Calcined sodium silicate shows excellent catalytic activity in the first run;

3however a considerable loss in catalytic activity is found when the catalyst is recycled for more than five times

(Guo

40et al., 2010). Sun et al. (2010) reported that the catalytic activity of

La₂O₃ loaded on ZrO₂ shows

39a correlation with their basic properties towards biodiesel production.
Other heterogenous catalysts that

show excellent catalytic activity as for biodiesel production are CaO/mesoporous silica (Samart et al., 2010), WO₃/ZrO₂ (Park et al., 2010), and sulfonated-multiwalled carbon nanotubes (Shu et al., 2009). Unfortunately, these catalysts are expensive and complicated to prepare, which limits their potential application in industrial scale operation. Clay materials are ubiquitous in nature while heterogeneous in composition and particle size (Bergaya and Lagaly, 2006; Zhou, 2010; Zhang et al., 2010). Different kinds of solid materials have been employed as heterogeneous catalysts or catalyst supports in biodiesel production as mentioned in the previous paragraph, however, information about the utilization of clay material such as bentonite as the catalyst or catalyst support for biodiesel preparation is very scarce. Therefore, in this study we utilized bentonite from Pacitan (East Java, Indonesia) as a catalyst for the biodiesel production because of its abundance. In the present investigation, the preparation of bentonite base catalyst for biodiesel production has been studied by optimizing KOH loading. Palm oil was used as the feedstock in

3 **biodiesel production due to** its abundance and **low price.**

312. Materials and methods 2.1. Materials Bentonite **used in this study** was **obtained from**

Pacitan, East Java, Indonesia. The elemental analysis of the bentonite was conducted

36 **using an Atomic Absorption Flame Emission Spectrophotometer (AA-6200, Shimadzu), and the**

results were as follow: Al 38.93%, Si 46.81%, Fe 3.24%, Ca 3.15%, Mg 0.41%, K 0.17%, Na 0.42%, and Mn 0.03%. Initially, the bentonite was immersed in hydrogen peroxide solution (30%) at 30 °C for 24 h to remove organic impurities. The ratio between hydrogen peroxide solutions to bentonite was 2:1.

12 **Then the mixture was** gently **heated in** a boiling **water bath**

to remove excess hydrogen peroxide and subsequently the solution was separated from the bentonite. Then the purified bentonite was suspended in distilled water and allowed to settle, the ratio of purified bentonite to distilled water was 1:4. After the water was removed, the purified bentonite was dried in force-circulation oven at 110 °C

6 **until its moisture content** reached **10%**. Subsequently, **the dried** bentonite **was** crushed **using**

a JANKE & KUNKEL micro hammer mill to obtain powdered bentonite with particle size 80/100 mesh. Refined palm oil (Bimoli) was used as raw material for biodiesel production. Analytical grade methanol and potassium hydroxide were

15 **obtained from Sigma Aldrich. Methyl heptadecanoate** and **standard** reference for FAME **analysis**

(methyl palmitate, methyl myristate, methyl oleate, methyl stearate and methyl linoleate) were from Fluka. 2.2. Catalyst preparation A series of KOH/bentonite catalysts for biodiesel production was prepared using the following procedure. The ratios between KOH and bentonite were 1:20, 1:10, 1:5, 1:4, 1:3, and 1:2. The preparation of catalysts was conducted in a three

14-neck round bottom flask (500 mL) equipped with a reflux condenser, temperature indicator, and

mechanical stirrer. The impregnation of bentonite with KOH was conducted at

7a temperature of 60 °C for 24 h

under continuous stirring. After completing the impregnation process, the slurry

1 was dried in an oven at 110 °C for 24 h to remove water. The catalyst was then calcined in

a tubular muffle furnace at a temperature of 400 °C for 5 h. 2.3. Catalyst characterization Surface analysis of the bentonite and catalysts was examined by nitrogen adsorption at its boiling point using a Quadrasorb SI. Prior to the nitrogen adsorption measurement, the sample was degassed at 150 °C under vacuum condition for 24 h. The BET surface area was calculated using the standard BET equation

30 in the relative pressure (p/p_0) range of 0.06 to 0.

3.

21 Powder X-ray diffraction (XRD) patterns of bentonite and the catalysts were recorded on a Rigaku Miniflex

Goniometer at 30 kV and 15 mA, using Cu K α radiation at a step size of 0.01°. Qualitative analysis of bentonite and the catalysts was conducted by the FTIR method using the KBr technique. FTIR analysis was carried out on a Shimadzu 8400 S FTIR instrument in wavenumber range of 4000–500 cm⁻¹. 2.4.

3 Transesterification of palm oil Transesterification of palm

23 oil was carried out in a three-neck round bottom flask (500 mL) equipped with a reflux condenser,

temperature indicator, and mechanical stirrer. The reactor was placed in a controlled water bath heater. A known amount of catalyst (3– 27 g) was added to a known

13 **volume of methanol. The mixture was then heated to the desired temperature**

(60 °C) in a controlled temperature water bath. Subsequently, palm oil was added into the mixture under vigorous stirring (500 rpm). The molar ratio of methanol to oil used in this study was 6 and the transesterification reaction was carried out

34 **for 1–6 h. At the end of the reaction time, the**

solution was centrifuged at a relative centrifugal force of 2054 g for 10 min. After centrifugation, the glycerin and biodiesel

14 **layers were separated. The biodiesel phase was washed with water (the**

ratio of wash water to biodiesel was 2), decanted and heated at 105 °C to remove water and methanol. 2.5. Determination of biodiesel yield The composition of the biodiesel produced by

2 **transesterification of palm oil and methanol using bentonite as a solid catalyst**

was determined using gas chromatography (GC-17A Shimadzu fitted with a DB-Wax capillary column (Agilent JW scientific) and FID (flame ionization detector)). Helium was used as the carrier gas.

11 **Methyl heptadecanoate was used as the internal standard. Peaks of methyl esters were identified by comparing them with the reference standards.** The injector **and**

35 **detector temperatures were 240 °C and 280 °C, respectively. The initial oven temperature was**

80 °C with an equilibration time of 3 min. After an isothermal period, the column oven was heated

20 **at a rate of 10 °C/min to 270 °C and held for 20 min. The yield of biodiesel was**

determined using the following equation $\text{weight of biodiesel} \times \text{total weight \% of FAME in sample yield } \delta\% = \text{weight of palm oil} \times 100 \delta1\%$ where FAME is

17 **fatty acid methyl esters. The physical properties of biodiesel produced in**

this experiment were determined according to the ASTM standard (kinematic viscosity: ASTM D.445-10, 2010; pour point: ASTM D.97, 2010; flash point: ASTM D.93, 2010; cetane index: ASTM D.613, 2010; and specific gravity: ASTM D.1298, 2005).

413. Results and discussion 3.1. Surface analysis and XRD measurement of bentonite and

17catalyst The BET surface area of the catalyst

decreased with increasing KOH loading (Fig. 1a). During the impregnation, the KOH molecules filled the available pores in the bentonite, leading to a

2decrease of the surface area of the catalyst.

By increasing the ratio of KOH to bentonite, the number of KOH molecules that occupy the available pores in the bentonite also increased, and this phenomenon significantly decreased the BET

24surface area of the catalyst. This indicated that the presence of

KOH molecules on the surface of the bentonite particles, and on the surface of the pores within the bentonite particles, and some KOH were probably converted to K₂O during calcination. Narrowing of the hysteresis curve of the adsorption isotherm (Fig. 1a) was an indication of the change in pore structure of bentonite from a mesoporous material to a nonporous structure after loading with KOH. A shift in

4pore sizes to larger pore diameters

led to a lower catalyst surface area.

4The major part of the KOH/bentonite catalyst volume was occupied by pores

larger than 5 nm (KOH/bentonite 1:20), 8 nm (KOH/bentonite 1:10), and 10 nm for the 1:5, 1:4 and 1:3 catalysts. A nonporous structure was observed for the KOH/bentonite 1:2 catalyst. These pore size distributions (Fig. 1b) are in agreement with the nitrogen adsorption isotherms. The FTIR spectrum of the bentonite (Fig. 2) reveals the presence of functional groups such as Al(Mg

26) **O–H stretching** (3614 cm^{-1}), **H–O–H stretching** (3360 cm^{-1}), **H–O–H bending**

(1670 cm^{-1}), Si–O–Si stretching (1061 cm^{-1}), OH bending bounded Fe^{3+} and Al^{3+} (921 cm^{-1}), and Si–O stretching (789 cm^{-1}). FTIR analysis showed that F.E. Soetaredjo et al. / Applied Clay Science 53 (2011) 341–346 343 the addition of KOH affected the structure of the bentonite network. The intensity of the Al(Mg)–O–H stretching group increased with an increased KOH loading. Also, a shift of absorption band of this group from 3614 cm^{-1} to higher wavenumbers indicated the presence of a new functional group in the catalysts being investigated (Al–O–K group or compound). A band at about 3430 cm^{-1} indicates the presence of

8 **the stretching vibration of the Al–O–K group**

(Xie and Lie, 2006). The XRD patterns of raw bentonite and KOH/bentonite catalyst (1:20 and 1:4) are given in Fig. 3.

27 **Reflections relative to the planes (001), (003) and (130–200) confirmed the presence of**

montmorillonite in the raw bentonite sample (Patel et al., 2007). The d_{100} value for raw bentonite was 1.43 nm.

1 **As the KOH loading ratio increased, the**

crystallinity of the catalyst increased.

1 **When the loading amount of KOH was increased to 1:20, the**

XRD pattern of the catalyst was still quite similar to that of the raw bentonite sample, and a new phase of K_2O began to appear. Here, the structure of bentonite still could be observed, and the d_{100} value shifted from 1.43 to 1.67 nm. The formation of K_2O is a strong indication that the KOH was not well Fig. 1. (a) Nitrogen sorption isotherms of bentonite and KOH/bentonite catalysts, (b) Pore size distribution of bentonite and KOH/bentonite catalysts. Fig. 1 (continued). dispersed on the bentonite surface or structure. During calcinations, potassium hydroxide was converted to K_2O as indicated in the XRD pattern. Reflections observed around $2\theta = 31^\circ, 39^\circ, 51^\circ, 55^\circ$ and 62° belong to the K_2O phase (Noiroj et al., 2009). Fig. 2. FTIR spectra of bentonite and KOH/bentonite catalysts. 3.2. Activity test of KOH/bentonite In order to investigate the activity of KOH/bentonite catalyst on the transesterification of palm oil, a series of experiments was conducted. Since the reaction mixture was not fully miscible at 60 $^\circ\text{C}$, the stirrer speed was kept constant at 750 rpm in order to increase the dispersion of the mixture.

103.2.1. Effect of KOH/ bentonite loading

The catalytic

10effect of KOH/ bentonite loading on transesterification

was investigated from the percentage of yield of fatty acid methyl ester. The experimental conditions for studying the effect of KOH/bentonite loading on the transesterification reaction were: the amount of catalyst at

243% (based on the weight of palm oil),

18methanol to oil molar ratio of 6 :1, reaction time of 3 h, and the reaction temperature at 60 °C. The

results clearly indicate that the amount of KOH loaded in bentonite affected the conversion of palm oil into biodiesel (Table 1). Increasing the loading amount of KOH from 5% (KOH/bentonite 1:20) to 25% (KOH/bentonite 1:4) also increased the yield of biodiesel. However, further increase of the loading amount of KOH/bentonite from 25% to 50% (KOH/bentonite 1:2) significantly decreased the conversion of palm oil into biodiesel. The highest yield (90.7%) was obtained at 25% KOH loading. A similar result was obtained by Noiroj et al. (2009) in the transesterification of palm oil using KOH/Al₂O₃ and KOH/NaY as catalysts. F.E. Soetaredjo et al. / Applied Clay Science 53 (2011) 341–346 345 Fig. 3. The XRD patterns for bentonite and KOH/bentonite catalyst. By increasing the KOH loading from 5% to 25%, the number of K₂O active sites in the catalyst also increased leading to an increase in the yield of biodiesel. However, further increases in KOH loading (higher Table 1 The effect of different process variables on the yield of biodiesel.

KOH:bentonite Reaction time Amount of catalyst Yield of biodiesel ratio (h) (%) (%) 1:20 3 3 1:10 3 3 1:5 3 3 1:4 3 3 1:3 3 3 1:2 3 3 1:4 1 3 1:4 2 3 1:4 3 3 1:4 4 3 1:4 5 3 1:4 6 3 1:4 3 1 1:4 3 2 1:4 3 3 1:4 3 4 1:4 3 5 1:4 3 6 1:4 3 7 1:4 3 8 1:4 3 9 43.51 ± 3.21 57.37 ± 4.11 68.46 ± 4.23 90.70 ± 2.47 81.48 ± 4.92 50.21 ± 2.53 15.32 ± 2.49 64.17 ± 4.58 90.70 ± 2.47 88.91 ± 3.22 90.63 ± 2.50 89.48 ± 2.41 52.74 ± 5.21 79.52 ± 4.32 90.70 ± 2.47 89.98 ± 3.11 90.41 ± 2.05 90.83 ± 3.08 90.56 ± 3.12 90.43 ± 2.97 91.22 ± 2.58 Average of three independent measurements. than 25%) resulted in a decreased yield of biodiesel. With high levels of KOH, the interactions between KOH and the internal layer of bentonite (Al–O–H stretching groups) were excessive and during the calcinations, a

10new phase of Al–O–K compound

was formed. This

5 **new phase** compound (**Al–O–K**) has lower catalytic activity and basicity than the **K₂O phase**

(Noiroj et al., 2009). When a high concentration of the

5 **Al–O–K compound was formed, the** catalytic activity of **the**

catalyst became lower, leading to a decrease in the biodiesel yield. 3.2.2. Effect of reaction time The operating conditions used to study

38 **the effect of reaction time on biodiesel yield** were **similar to**

those used in Section 3.2.1. Since

12 **the highest yield of biodiesel was obtained** with KOH/bentonite **1:4** catalyst, this **ratio**

was used in subsequent experimental studies. The optimum reaction time for the biodiesel production was 3 h. During the first three hours the

9 **yield of biodiesel** increased **with** the **increase in**

reaction time (Table 1). After three hours, the yield of biodiesel was almost constant as the equilibrium conversion had been reached.

93.2.3. **Effect of the catalyst amount** To determine **the effect of catalyst on the yield of biodiesel,**

the amount of catalyst was varied between 1% and 9% by weight based on the amount of palm oil. The yield of biodiesel increased from 52.7% at 1% KOH/bentonite catalyst to 90.7% at 3% catalyst, with little further change in yield between 3% and 9% catalyst (Table 1). The increase

13 **in the conversion of palm oil** into **fatty acid methyl esters**

between 1% and 3% catalyst addition was

33due to an **increase in the number of active basic sites** (K₂O) in **the reaction**

system. Furthermore, a slight increase is shown with a change in the amount of catalyst from 3% to 9%. Transesterification reaction of triglyceride with methanol is a reversible reaction; to alter the reaction into the right hand site to produce methyl esters one should consider Le Chatelier's principle. Therefore, when the amount of catalyst provides sufficient basic sites and the reaction has already reached an equilibrium condition, increasing the amount of catalyst does not affect biodiesel yield significantly. 3.2.4. Catalyst stability Reusability and stability are very important criteria for industrial application of KOH/bentonite as a heterogeneous catalyst

28for **biodiesel production (Liu et al., 2007; Silva et al., 2010)**. In this study **the reusability of**

KOH/bentonite catalyst was examined by carrying out three reaction cycles. For fresh catalyst (KOH/bentonite 1:4) the maximum conversion was 90.7%. After separation from the liquid mixture (biodiesel, glycerin, methanol, and water), the catalyst was repeatedly washed with methanol (at least 4 times) and re-calcined at

7a **temperature of 300 °C for 5 h. A**

subsequent cycle was started with Fig. 4. Multiple cycle test of catalyst deactivation (KOH/bentonite 1:4). Table 2 Comparison of the properties of biodiesel produced in this experiment with the standard issued by Indonesia National Standard (SNI-04-7182-2006). Properties Biodiesel produced SNI Kinematic viscosity at 40 °C (cSt) Specific gravity (15 °C) Cetane index Flash point (°C) Pour point (°C) Heating value (MJ/kg) 4.2 0.88 62 170 16 38.1 1.9–6.0 0.86–0.90 N45 Min 65 Max 18 – fresh reactants. For the second and the third cycles, the maximum yield of biodiesel was less than 85% (Fig. 4). Here deactivation of basic sites occurred; some of the possible basic sites were poisoned during the transesterification reaction. These results are similar to those obtained by Silva et al. (2010) and Liu et al. (2007). 3.3. Biodiesel characteristics Biodiesel produced from palm oil using KOH/bentonite as a catalyst fulfilled the standard for biodiesel (Table 2). Fuels with low cetane index make the engine starting difficult. There is also an increase of noise and smoke in exhaust gas. Since the cetane index of the biodiesel produced in this experiment was above 45, the diesel engine will operate better using this biodiesel as a fuel. Viscosity of fuel gives a significant effect on the performance of injector and fuel atomization. If the viscosity is lower than 1.9, the fuel

22may not provide sufficient lubrication for the **fuel injection**

pump, however if the fuel is too viscous it results in

22larger droplets in **injection which can cause poor combustion.**

Flash point temperature relates to the ignition of the fuel, and the minimum value of this property is required for proper safety and handling of the fuel. Since the flash point of the biodiesel from palm oil with KOH/bentonite as catalyst was higher than the Indonesia National Standard (2006), this fuel is safe for handling and storage for some period of time. Therefore it can be applied as a substitute fuel for diesel engines. 4. Conclusion A heterogeneous catalyst KOH/bentonite can be used

2as a solid based catalyst for biodiesel production via transesterification of palm oil. The catalyst synthesized with

25% KOH loading gave the best performance for biodiesel production. The operating condition to produce the highest yield of biodiesel was: reaction time 3 h, amount of catalyst 3%, methanol to oil ratio 6, and the reaction temperature at 60 °C. Acknowledgements We thank to

19Dr David Barkley from N. Simonson & Company (<http://www.virtlab.com>) for assistance in language editing.

Substantial contributions in terms of suggestions and comments from anonymous reviewers and editor have improved the quality of this manuscript which deserves appreciation. References ASTM Standard D1298, 2005. Standard Test Methods for Density, Relative Density (Specific Gravity) or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method. ASTM International, West Conshohocken, PA. doi:10.1520/D1298-99R05. www.astm.org. ASTM Standard D445-10, 2010. Standard Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity). ASTM International, West Conshohocken, PA. doi:10.1520/D0445-10. www.astm.org. ASTM Standard D613, 2010. Standard Test Methods for Cetane Number of Diesel Fuel Oil. ASTM International, West Conshohocken, PA. doi:10.1520/D0163-10A. www.astm.org. ASTM Standard D93, 2010. Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester. ASTM International, West Conshohocken, PA. doi:10.1520/D0093-10A. www.astm.org. ASTM Standard D97, 2010. Standard Test Method for Pour Point of Petroleum Products. ASTM International, West Conshohocken, PA. doi:10.1520/D0097-09. www.astm.org. Bergaya, F., Lagaly, G., 2006. General introduction: clays, clay minerals, and clay science. In: Bergaya, F., Theng, B.K.G., Lagaly, G. (Eds.), Handbook of Clay Science: Development in Clay Science vol. 1. Elsevier, Amsterdam. Dhainaut, J., Dacquin, J.P., Lee, A.F., Wilson, K., 2010. Hierarchical macroporous–mesoporous SBA-15 sulfonic acid catalysts for biodiesel synthesis. Green Chem. 12, 296–303. Feng, Y., He, B., Cao, Y., Li, J., Liu, M., Yan, F., Liang, X., 2010. Biodiesel production using cation-exchange resin as heterogeneous catalyst. Bioresour. Technol. 101, 1518–1521. Gao, L., Teng, G., Lv, J., Xiao, G., 2010. Biodiesel synthesis catalyzed by the KF/Ca–Mg–Al hydrotalcite base catalyst. Energy Fuels 24, 646–651. Guo, F., Peng, Z.G., Dai, J.Y., Xiu, Z.L., 2010. Calcined sodium silicate as solid base catalyst for biodiesel production. Fuel Process. Technol. 91, 322–328. Hsieh, L.S., Kumar, U., Wu, J.C.S., 2010. Continuous production of biodiesel in a packed-bed reactor using shell-core structural Ca(C₃H₇O₃)₂/CaCO₃ catalyst. Chem. Eng. J. 158, 250–256. Indonesia National Standard, 2006, Standard of Biodiesel SNI-04-7182-2006, Jakarta. Kim, M., Yan, S., Salley, S.O., Ng, K.Y.S., 2010. Competitive transesterification of soybean oil with mixed methanol/ethanol over heterogeneous catalysts. Biores. Technol. 101, 4409–4414. Leung, D.Y.C., Wu, X., Leung, M.K.H., 2010. A review on biodiesel production using catalyzed transesterification. Appl. Energy 87, 1083–1095. Liu, Y., Lotero, E., Goodwin Jr., J., Mo, X.,

2007. Transesterification of poultry fat with methanol using Mg–Al hydrotalcite derived catalysts. *Appl. Catal. A Gen.* 331, 138–148. Liu, C., Lv, P., Yuan, Z., Yan, F., Luo, W., 2010. The nanometer magnetic solid base catalyst for production of biodiesel. *Renewable Energy* 35, 1531–1536. Noiroj, K., Intarapong, P., Luengnaruemitchai, A., Jai-In, S., 2009. A comparative study of KOH/Al₂O₃ and KOH/NaY catalysts for biodiesel production via transesterification from palm oil. *Renewable Energy* 34, 1145–1150. Ong, Y.K., Bhatia, S., 2010. The current status and perspectives of biofuel production via catalytic cracking of edible and non-edible oils. *Energy* 35, 111–119. Park, Y.M., Lee, J.Y., Chung, S.H., Park, I.S., Lee, S.Y., Kim, D.K., Lee, J.S., Lee, K.Y., 2010. Esterification of used vegetable oils using heterogeneous WO₃/ZrO₂ catalyst for production of biodiesel. *Bioresour. Technol.* 101, S59–S61. Patel, H.A., Somani, R.S., Bajaj, H.C., Jasra, R.V., 2007. Synthesis and characterization of organic bentonite using Gujarat and Rajasthan clays. *Curr. Sci.* 92, 1004–1009. Ranganathan, S.V., Narasimhan, S.L., Muthukumar, K., 2008. An overview of enzymatic production of biodiesel. *Bioresour. Technol.* 99, 3975–3981. Samart, C., Chaiya, C., Reubroycharoen, P., 2010. Biodiesel production by methanolysis of soybean oil using calcium supported on mesoporous silica catalyst. *Energy Convers. Manag.* 51, 1428–1431. Saravanan, S., Nagarajan, G., Lakshmi Narayana Rao, G., Sampath, S., 2009. Biodiesel production from high FFA crude rice bran oil and investigation on its properties as CI engine fuel. *Int. J. Oil. Gas Coal Technol* 2, 389–398. Shiu, P.J., Gunawan, S., Hsieh, W.H., Kasim, N.S., Ju, Y.H., 2010. Biodiesel production from rice bran by a two-step in-situ process. *Bioresour. Technol.* 101, 984–989. Shu, Q., Zhang, Q., Xu, G., Wang, J., 2009. Preparation of biodiesel using s-MWCNT catalysts and the coupling of reaction and separation. *Food Bioprocess Technol* 87, 164–167. Silva, C.C.C.M., Ribeiro, N.F.P., Souza, M.M.V.M., Aranda, D.A.G., 2010. Biodiesel production from soybean oil and methanol using hydrotalcites as catalyst. *Fuel Process. Technol.* 91, 205–210. Sun, H., Ding, Y., Duan, J., Zhang, Q., Wang, Z., Lou, H., Zheng, X., 2010. Transesterification of sunflower oil to biodiesel on ZrO₂ supported La₂O₃ catalyst. *Bioresour. Technol.* 101, 953–958. Talukder, M.M.R., Wu, J.C., Fen, N.M., Melissa, Y.L.S., 2010. Two-step lipase catalysis for production of biodiesel. *Biochem. Eng. J.* 49, 207–212. Xie, W., Lie, H., 2006. Alumina supported potassium iodide as heterogeneous catalyst for biodiesel production from soybean oil. *J. Mol. Catal. A. Chem.* 255, 1–9. Zabeti, M., Daud, W.M.A.W., Aroua, M.K., 2010. Biodiesel production using alumina-supported calcium oxide: an optimization study. *Fuel Process. Technol.* 91, 243–248. Zhang, D., Zhou, C.H., Lin, C.X., Tong, D.S., Yu, W.H., 2010. Synthesis of clay minerals. *Appl. Clay Sci.* 50, 1–11. Zhou, C.H., 2010. Emerging trends and challenge in synthetic clay-based materials and layered double hydroxides. *Appl. Clay Sci.* 48, 1–4. Zhou, C.H.C., Beltramini, J.N., Fan, Y.X., Lu, G.Q., 2008. Chemoselective catalytic conversion of glycerol as a biorenewable source to valuable commodity chemicals. *Chem. Soc. Rev.* 37, 527–549. Author's personal copy 342 Author's personal copy F.E. Soetaredjo et al. / *Applied Clay Science* 53 (2011) 341–346 Author's personal copy 344 Author's personal copy F.E. Soetaredjo et al. / *Applied Clay Science* 53 (2011) 341–346 Author's personal copy 346 Author's personal copy F.E. Soetaredjo et al. / *Applied Clay Science* 53 (2011) 341–346